

ՎԱՃԱՌՎՈՒՄ Է

Շինարարական վերելակ
2007 թվականի արտադրության, SCD 200/200 GD 090109 մակնիշի:
Բարձրությունը՝ 65 մետր,
բեռնամբարձությունը կազմում է 1 տոննա:

Գինը՝ 10,000,000 ՀՀ դրամ









SC型施工升降机防坠安全器

特种设备型式试验合格证 TX F440-06-06 0005

型号 SAJ40-1.2 编号 7B-284C

额定载荷 40 KN 额定动作速度 1.2 m/s

标定动作速度 1.0 m/s

有效标定年限 2年 出厂日期 20 07 08

昆山市京浦机械制造有限公司制造

厂址 昆山市蓬朗镇马塘 电话 0512-57611398

Operation Rules of SC/SCD-type Building Elevator

1. Drivers must be qualified and trained by the government department.
2. Should inspect steel cable, the electric appliance, and safety device of each part of movement organ works normally.
3. The load of this machine must be carried available, or strictly prohibited to over the rated load.
4. When elevators running, strictly prohibit the personnel, the cargo should out of the closed cage.
5. When elevators running, strictly prohibit the personnel to enter the bottom compartment of the suspension cage.
6. If elevators do not work, the sound of red or light vibration or great and stop in motion, and inspect, and strictly prohibit the appliances work in bad state.
7. If heavy weathers or force wind over 5 class, the elevator should not work, and stop into power line and switch off.
8. The elevators should be carried for daily inspection, weekly inspection and monthly inspection, and the tripper should be tested every three months for fall protection.
9. When shift-changing, driver must complete records, when off duty, stop into cage to remove the bottom cage, and switch off.

Parameter Table of SC/SCD-type Building Elevator

Product applied standards: GB10060-2011 Number: SC100/1000 Date: 2011.10.11

Item	Unit	SC100	SC100/1000	SC100/1000	SC100/1000	SC100/1000	SC100/1000
Type							
Rated Load	kg	1000	1000/12	2500	3000/12	3000	3000/12
Personnel allowed	person	12	12/12	24	24/12	24	24/12
Headroom of suspension cage (long x width x height)	meter	2x1.3x2.5	2x1.3x2.5	2x1.3x2.5	2x1.3x2.5	2x1.3x2.5	2x1.3x2.5
Cage height	meter	1.90	1.90	1.90	1.90	1.90	1.90
Elevating speed	m/min	3.0/3.5/4.0	3.0/3.5/4.0	3.0/3.5/4.0	3.0/3.5/4.0	3.0/3.5/4.0	3.0/3.5/4.0
Governor type							
Weight of suspension cage	kg	1370	1370/12	1370	1370/12	1370	1370/12
Counterweight weight	kg	5	0	128	128	128	128
Standard weight	kg	128	128	128	128	128	128
Standard Use Length	mm	1900	1900	1900	1900	1900	1900
Power	KW	2x0.5/1	2x0.5/1	2x0.5/1	2x0.5/1	2x0.5/1	2x0.5/1
Power supply	KW	2x0.5/1	2x0.5/1	2x0.5/1	2x0.5/1	2x0.5/1	2x0.5/1
Capacitance	KW	26	2x26	26	2x26	26	2x26

Manufacturer: Foshan Nanhai Guanyu Elevator Co., Ltd.
 Address: North of Pingnan, Wuzhou Stage, Nanhai District, Foshan City, Guangdong Province, China
 Post code: 528251
 Tel: 0757-86198321 86785036
 Fax: 0757-86715882

ConverseBank



Mobile: 098-49-44-55



E-mail: ManukyanArtur@conversebank.am



Address: Vazgen Sargsyan 26/1



Website: www.conversebank.am

